

# REMOVE 9000 Powder Coat Dissolver

---

1101 W. Stevens Ave. Unit 176  
Santa Ana  
California 92647  
United States

Phone: 248-765-9946

"REMOVE"™ Room Temperature Powder Coat Remover, Removes Powder Coating from Hooks, Racks and Rework[https://www.mileschemicalsolutions.com/Remove\\_Powder\\_Coat\\_Remover.html](https://www.mileschemicalsolutions.com/Remove_Powder_Coat_Remover.html)"Remove" Powder Coat Remover-Removes Powder Coating from Hooks, Racks & Powder Coat Rework at Room Temperature, Safe for use on All Metals. Remove is an Eco-friendly & Operator friendly, Powder Coating Remover. Available as "Our Fastest" Powder Coating Stripper-REMOVE 9000-Liquid Dissolver or REMOVE 9000 De-laminator for (Immersion-Dip) | REMOVE #9001-Gel for (Brush-on applications) & REMOVE #9002 De-laminator Thixotropic-Stripper (Brush or Dip) Formula . Remove 9000-Liquid Powder Coat Remover/Dissolver T E C H N I C A L D A T A S H E E T Description: Visit site at:

<http://www.removepowdercoatpaint.com> Remove 9000-Liquid Powder Coating Remover/Dissolver is a Non-Methylene Chloride Formula used at Room Temperature to Dissolve Powder Coating. Remove 9000-Liquid Dissolver Quickly Dissolves Powder Coating in an Immersion Application. It is a Non-Hazardous, Ready-to-Use Powder Stripper that Dissolves All Types of Powder Coatings, including TGIC and Epoxy Powder Coating, Varnishes & Adhesives. Operator Friendly, Non-Caustic, Non-Acid and is a Nearly Odorless Powder Coat Dissolver, Low-Odor formula. Directions: Agitate before Using. Immerse parts to be stripped in an immersion tank, drum or pail. Remove 9000 Dissolves Powder Coat in 15 minutes to 1-2 hours at Room Temperature, It's Aluminum & All Metal Safe. Formulated to Clean Powder Coating from Hooks, Racks and Coating Rework at Room Temperature . Strip time will vary depending on type of coating and coating film build. Mechanical Agitation is not required, however will accelerate stripping. Air agitation is not recommended: Air-(Oxygen will reduce solution life). Use No-Water with Remove 9000. Rinse parts after stripping with water. Not formulated for

---

brush-on applications. Available for purchase in 1-gallon Bottle, 5-gallon pail or 2

55-Gallon drum. Begin to reclaim coating rework and clean hooks in-plant today and save!  
[Place\\_Secure\\_Order\\_Here](#)

[Visit Website](#)  
[Email Friend](#)